HONDA

WJR 4025 WJR 2525





Excellent usability and cost performance


HONDA



Width is narrowed and the center of









body for easy lifting.



Equipped with mini 4-stroke Honda GX25/35 engine

Detachable nozzle holder

The nozzle and hose, which gets in the way when moving, can be contained neatly.



WJR4025T High-pressure type*





Operation box

Independent from the shoulder belt for more efficient operation.

		BASIC SPECIFICATIONS	WJR2525T
Model Type		WJR4025T WAFT	WJR25251 WAET
Frame Type		GCS	GCS
Dimensions L x W x H (mm)		400 x 495 x 695	390 x 495 x 615
Dry weight (kg)		12.5	12.0
Chemical tank capacity (L)		25	25
Pump	Туре	Plunger type	Plunger type
	Pressure in shut-off valve close condition (MPa)	4.0 / 6700 rpm	2.5 / 7000 rpm
	Suction amount (L/min)	8.0 / 6700 rpm	6.6 / 7000 rpm
Engine	Model / Type	GX35T / Air-cooled single-cylinder 4-stroke OHV	GX25T / Air-cooled single-cylinder 4-stroke OHV
	Displacement (cm³)	35.8	25.0
	Engine net power / Engine speed (kW/rpm)	1.0 / 7000	0.72 / 7000
	Maximum net torque / Engine speed (kW/rpm)	1.6 / 5500	1.0 / 5000
	Fuel tank capacity (L)	0.63	0.53
	Starting system	Recoil	

*Note: Specifications and included attachments are subject to change without prior notice.

Tanauan City, Batangas